

## Calibration Certificate Requirements

The following descriptions explain our calibration certs and what it entails. Please indicate the category that best fits your needs. We will maintain this information in our database and apply it to all calibrations. All Calibrations performed by JJ Calibrations are traceable to the SI or NIST. All units tested are calibrated to OEM specifications and accuracies, and come with certificate of calibration and a calibration sticker.

and accuracies, and come with		calibration sticker.	specifications
Traceable Calibration with Tolerance acceptance based on OEM to	h Measurement Data Certificate	e	
	sed on customer request (default 12 m) Returned In/Out of Tolerance		
	ith Measurement Data and Calc lerances/specifications. Simple acceptance is use	ulated Uncertianties (ISO 17025) d on calibration certificates*	<b>ACCREDITED</b> 723.01
		using Simple Acceptance to OEM specs	
*Uncertainties calculated include UUT. Determ	nation of acceptance to specified/OEM tolerand	ce based on accuracy alone, without the inclusion of unce	rtianty of data point
Accredited Calibration w Guardbanding using calculated uncert		ulated Uncertianties (ISO 17025)	ACCREDITED 723.01
Stated Unit As Received / As As Found / As Left Data Calculated Uncertainties of	sed on customer request (default 12 m) Returned In/Out of Tolerance us each data point be communicated to JJ before cali	sing Guardbanding guidelines	
Mixed			
requirements will need to be spe		rmation. If this is specified, certificate of it at the time it is sent in for calibration. V e given an updated request.	
Company Name		Date	
Name	Signa	ture	